

Temperature Compensated Zener Reference Diode Series



1N4565UR thru 1N4584AUR, 1N4565AUR-1 thru 1N4584AUR-1

Features

- Available in JAN, JANTX, JANTXV and JANS per MIL-PRF-19500/452
- 6.4 Volt Nominal Zener Voltage $\pm 5\%$
- Metallurgically Bonded

Maximum Ratings

Operating & Storage Temperature: -65°C to $+175^{\circ}\text{C}$

DC Power Dissipation: 500mW @ $+50^{\circ}\text{C}$

Power Derating: 4 mW / $^{\circ}\text{C}$ above $+50^{\circ}\text{C}$

REVERSE LEAKAGE CURRENT

$I_R = 2\ \mu\text{A}$ @ 25°C & $V_R = 3\ \text{Vdc}$





Electrical Specifications @ $+25^{\circ}\text{C}$ (Unless Otherwise Specified)

JEDEC Type Number	Zener Test Current	Effective Temperature Coefficient	Voltage Temperature Stability ($3V_{ZT}$ maximum) (Note 1)	Temperature Range	Maximum Dynamic Zener Impedance (Note 2)
	mA	$\%/^{\circ}\text{C}$	mV	$^{\circ}\text{C}$	Ohms
1N4565UR, -1	0.5	0.01	48	0 to $+75^{\circ}\text{C}$	200
1N4565AUR, -1	0.5	0.01	100	-55 to $+100^{\circ}\text{C}$	200
1N4566UR, -1	0.5	0.005	24	0 to $+75^{\circ}\text{C}$	200
1N4566AUR, -1	0.5	0.005	50	-55 to $+100^{\circ}\text{C}$	200
1N4567UR, -1	0.5	0.002	10	0 to $+75^{\circ}\text{C}$	200
1N4567AUR, -1	0.5	0.002	20	-55 to $+100^{\circ}\text{C}$	200
1N4568UR, -1	0.5	0.001	5	0 to $+75^{\circ}\text{C}$	200
1N4568AUR, -1	0.5	0.001	10	-55 to $+100^{\circ}\text{C}$	200
1N4569UR, -1	0.5	0.0005	2.5	0 to $+75^{\circ}\text{C}$	200
1N4569AUR, -1	0.5	0.0005	5	-55 to $+100^{\circ}\text{C}$	200
1N4570UR, -1	1.0	0.01	48	0 to $+75^{\circ}\text{C}$	100
1N4570AUR, -1	1.0	0.01	100	-55 to $+100^{\circ}\text{C}$	100
1N4571UR, -1	1.0	0.005	24	0 to $+75^{\circ}\text{C}$	100
1N4571AUR, -1	1.0	0.005	50	-55 to $+100^{\circ}\text{C}$	100
1N4572UR, -1	1.0	0.002	10	0 to $+75^{\circ}\text{C}$	100
1N4572AUR, -1	1.0	0.002	20	-55 to $+100^{\circ}\text{C}$	100
1N4573UR, -1	1.0	0.001	5	0 to $+75^{\circ}\text{C}$	100
1N4573AUR, -1	1.0	0.001	10	-55 to $+100^{\circ}\text{C}$	100
1N4574UR, -1	1.0	0.0005	2.5	0 to $+75^{\circ}\text{C}$	100
1N4574AUR, -1	1.0	0.0005	5	-55 to $+100^{\circ}\text{C}$	100
1N4575UR, -1	2.0	0.01	48	0 to $+75^{\circ}\text{C}$	50
1N4575AUR, -1	2.0	0.01	100	-55 to $+100^{\circ}\text{C}$	50
1N4576UR, -1	2.0	0.005	24	0 to $+75^{\circ}\text{C}$	50
1N4576AUR, -1	2.0	0.005	50	-55 to $+100^{\circ}\text{C}$	50
1N4577UR, -1	2.0	0.002	10	0 to $+75^{\circ}\text{C}$	50
1N4577AUR, -1	2.0	0.002	20	-55 to $+100^{\circ}\text{C}$	50
1N4578UR, -1	2.0	0.001	5	0 to $+75^{\circ}\text{C}$	50
1N4578AUR, -1	2.0	0.001	10	-55 to $+100^{\circ}\text{C}$	50
1N4579UR, -1	2.0	0.0005	2.5	0 to $+75^{\circ}\text{C}$	50
1N4579AUR, -1	2.0	0.0005	5	-55 to $+100^{\circ}\text{C}$	50
1N4580UR, -1	4.0	0.01	48	0 to $+75^{\circ}\text{C}$	25
1N4580AUR, -1	4.0	0.01	100	-55 to $+100^{\circ}\text{C}$	25
1N4581UR, -1	4.0	0.005	24	0 to $+75^{\circ}\text{C}$	25
1N4581AUR, -1	4.0	0.005	50	-55 to $+100^{\circ}\text{C}$	25
1N4582UR, -1	4.0	0.002	10	0 to $+75^{\circ}\text{C}$	25
1N4582AUR, -1	4.0	0.002	20	-55 to $+100^{\circ}\text{C}$	25
1N4583UR, -1	4.0	0.001	5	0 to $+75^{\circ}\text{C}$	25
1N4583AUR, -1	4.0	0.001	10	-55 to $+100^{\circ}\text{C}$	25
1N4584UR, -1	4.0	0.0005	2.5	0 to $+75^{\circ}\text{C}$	25
1N4584AUR, -1	4.0	0.0005	5	-55 to $+100^{\circ}\text{C}$	25



NOTE 1: The maximum allowable change observed over the entire temperature range i.e., the diode voltage will not exceed the specified mV at any discrete temperature between the established limits, per JEDEC standard No. 5.

NOTE 2: Zener impedance is derived by superimposing on I_{ZT} A 60Hz rms a.c. current equal to 10% of I_{ZT} .





TYPICAL CHANGE OF TEMPERATURE COEFFICIENT WITH CHANGE IN OPERATING CURRENT




ZENER IMPEDANCE VS. OPERATING CURRENT

1N4565UR thru 1N4584AUR, 1N4565UR- thru 1N4584AUR-1



Outline Drawing



LEADED DESIGN DATA

CASE: DO – 213AA, Hermetically sealed glass case.
(MELF, SOD-80, LL34)

LEAD FINISH: Tin / Lead

POLARITY: Cathode end is banded.

MOUNTING POSITION: Any.

MOUNTING SURFACE SELECTION: The Axial Coefficient of Expansion (COE) Of this Device is Approximately +6 PPM/°C. The COE of the Mounting Surface System Should Be Selected To Provide A Suitable Match With This Device.

Aeroflex / Metelics, Inc.

975 Stewart Drive,
Sunnyvale, CA 94085
Tel: (408) 737-8181
Fax: (408) 733-7645

Sales: 888-641-SEMI (7364)

Hi-Rel Components

9 Hampshire Street,
Lawrence, MA 01840
Tel: (603) 641-3800
Fax: (978) 683-3264

www.aeroflex.com/metelics-hirelcomponents

www.aeroflex.com/metelics **metelics-sales@aeroflex.com**

Aeroflex / Metelics, Inc. reserves the right to make changes to any products and services herein at any time without notice. Consult Aeroflex or an authorized sales representative to verify that the information in this data sheet is current before using this product. Aeroflex does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by Aeroflex; nor does the purchase, lease, or use of a product or service from Aeroflex convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Aeroflex or of third parties.

Copyright 2010 Aeroflex / Metelics. All rights reserved.

ISO 9001: 2008 certified companies



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.